

Constructing your new cabin: Double skin

Please note: Insulation can be installed into floors, walls and ceiling cavity as required.

Step 1

Carefully unpack cabin and check all components are present.

Step 2

Ensure base is level and square. **EXTREMELY IMPORTANT!**

Step 3

Lay out green tanalised bearers for floor to sit on as shown in supplied plans.

Step 4

If your new cabin has four walls, separate wall components into four individual stacks corresponding with walls to avoid any unnecessary confusion later on!
Don't forget to subdivide the stacks into internal and external walls!!

Step 5

Start constructing your new cabin.

Step 6

When base of window height is reached place spacer timbers into cavity either side of window. Place window into position and carry on building using fixing plates to connect internal and external wall to timber spacers. Use the same method for the doors also.
On the larger cabins there will be additional spacers along the walls.

Step 7

Build up to gable ends then place ready cut roof purlins into position and fix with parts supplied.

Step 8

Nail internal roofing boards into position following supplied plans.

Step 9

Install roof insulation if required.

Step 10

Fix external roofing boards.

Step 11

Fix fascia boards

Step 12

Fix roof covering. See our [roof shingles fitting instructions](#).

Step 13

Fix floorboards into position with fixings supplied.

Step 14

Put kettle on and enjoy your new cabin.

Feel free to call our team if you have any questions on 0845 634 5025